

ADAM-6521 ADAM-6521S (New)

**Industrial Switch with 4
10/100 Mbps Ethernet Ports
& 1 Multi-mode Fiber Port**

**Industrial Switch with 4
10/100 Mbps Ethernet Ports
& 1 Single-mode Fiber Port**



CE FCC UL

Features

- Supports 1 port 100 Mbps multi/single-mode Fiber optic SC & 4-port 10/100 Mbps RJ-45 connectors
- Supports full/half duplex flow control
- Supports Integrated Loop-up engine
- Supports MDI/MDI-X auto crossover
- Provides broadcast storm protection
- Supports +10~ 30 V_{DC} voltage power input
- Provides surge protection 3,000 V_{DC} for power line
- Supports 4,000 V_{DC} Ethernet ESD protection
- Provides flexible mounting: DIN-rail, panel, piggyback
- Supports operating temperatures from -10 ~ 65° C

Introduction

ADAM-6521 and ADAM-6521S are industrial-grade Ethernet switch with a fiber optic port that makes it possible to expand industrial networks fast and cost-effectively. ADAM-6521 and ADAM-6521S of 1 fiber port and 4-RJ-45 ports. With fiber optics, you can prevent noise interfering with your system and implement transmission distances up to 15 km.

ADAM-6521 and ADAM-6521S are especially suited for industrial environments with Ethernet networking needs such as: semi-conductor factories, inventory control environments, assembly line and production and more.

Like other products in the ADAM® family, ADAM-6521 and ADAM-6521S can be mounted in three different ways: DIN rail, panel and piggyback, suitable for any industrial environment.

ADAM-6521 and ADAM-6521S support a wide voltage range of +10 ~ 30 V_{DC} over the terminal block, and 3,000 V_{DC} surge protection to protect it from being damaged by over-voltage. A wide operating temperature range from -10 to 65° C (14 ~ 149° F), makes it functional in harsh operating environments.

This six inclusive LED indicators make troubleshooting the ADAM-6521 and ADAM-6521S easier. Each port has a pair of LEDs that indicate link status and transmission speed. This function conveniently informs users of any collisions, the link status, power failure and data receipts for immediate on-site diagnostics.

Specifications

Communications

- **Standard** IEEE 802.3, 802.3u, 802.3x
- **LAN** 10/100Base-T, 100Base-FX
- **Transmission Distance** Ethernet: 100 m
Fiber
ADAM-6521: 2 km
ADAM-6521S: 15 km
- **Transmission Speed** Ethernet : up to 100 Mbps
Fiber : 100 Mbps

Interface

- **Connectors** 4 x RJ-45, 1 x SC type fiber connector
- **LED Indicators** Power, Link (100Base-FX), 100/10M (Ethernet)

Power

- **Power Connectors** 2-pin removable screw terminal
- **Power Consumption** ADAM-6521: Max.3 W
ADAM-6521S: Max.4 W
- **Power Input** Unregulated 10 ~ 30 V_{DC}

Mechanism

- **Dimensions(W x H x D)** 70 x 102 x 27 mm
- **Enclosure** ABS+PC with solid mounting hardware
- **Mounting** DIN 35 rail, stack, wall

Protection

- **ESD Protection** 4,000 V_{DC} (Ethernet)
- **Surge Protection** 3,000 V_{DC} (Power)

Environment

- **Operating Temperature** -10~65° C (14~149° F)
stack : -10~60° C (14~140° F)
- **Storage Temperature** -20~80° C (-4~176° F)
- **Operating Humidity** 20~95% (non-condensing)
- **Storage Humidity** 0~95% (non-condensing)
- **MTBF** 1,150,000 hrs

Certifications

- **Safety** UL 60950-1, CAN/CSA-C22.2 No.60950
- **EMC** U.S.A.: FCC Part 15 CISPR 22
EU: EN55011
EN55022 Class A,
EN61000-3-2/3
EN55024
IEC61000-4-2/3/4/5/6/8/11

- **Ingress Protection** IP30

Ordering Information

- **ADAM-6521** Industrial Switch with 4 10/100 Mbps Ethernet Ports & 1 Multi-Mode Fiber Port
- **ADAM-6521S** Industrial Switch with 4 10/100 Mbps Ethernet Ports & 1 Single-Mode Fiber Port